

CASE NO.: 1006.023
Serial No.: 10/062,655
June 11, 2003
Page 2

PATENT
Filed: February 1, 2002

cent. A1
sub B1
cont. A1
a transmitter within the remote control unit;
an actuator coupled to the window covering;
a receiver within the actuator, the receiver receiving at least one signal from the transmitter;

a wake-up signal amplifier electrically connected to the receiver for receiving a wake-up signal having a first frequency; and
475 Hz

38 KHz
a data signal amplifier electrically connected to the receiver for receiving a data signal having a second frequency lower than the first frequency, the data signal carrying information for moving the window covering.

sub B1
cont. A1
A2
7. (amended) A method for controlling a motorized window covering, comprising the acts of:

deactivating a data signal amplifier;
activating a wake-up signal amplifier; and
activating the data signal amplifier to process a data signal to move the window covering only in response to a wake-up signal being received by the wake-up signal amplifier, the wake up signal having a first frequency and the data signal having a second frequency different from the first frequency.

A3
sub B1
cont. A1
12. (amended) A system for controlling a motorized window covering, comprising:
an actuator mechanically coupled to an operator of the window covering;

1006-23.AMD

CASE NO.: 1006.023
Serial No.: 10/062,655
June 11, 2003
Page 3

PATENT
Filed: February 1, 2002

h
5B1
on to

a receiver within the actuator;

a wake-up signal amplifier electrically connected to the receiver for receiving a wake-up signal having a first frequency;

a data signal amplifier electrically connected to the receiver for receiving a data signal having a second frequency lower than the first frequency, the data signal carrying information for moving the window covering; and

a processor within the actuator, the processor including a program for controlling the actuator in response to at least one data signal.

1006-23.AMTD